



### Name

Frost Floor drain assembly medium duty with clamp adjustable 200mm grating square, small sump body cast iron vertical outlet BSP4

### Code

31.0044

### Description

Frost floor drain with 200mm square grating, small sump body and threaded outlet.

Supplied with a membrane clamp.

Untrapped assemblies are for use in unfinished, screeded or paved concrete floors such as parking areas, warehouses and plant rooms.

Connect to pipework using an adaptor.

Please note that the overall height of assemblies will vary according to membrane thickness.

Cast iron Grade EN-GJL-150 to BS EN 1561:1997

80%-97% recycled materials

100% recyclable

Ductile iron BS EN 1563 & 1564

Greater than 80% recycled materials

100% recyclable

Aluminium Grade LM 6 to BS EN 1559-4:1999

Greater than 90% recycled materials

100% recyclable

### Body Material

CAST IRON

### Body Type

UNTRAPPED

### Grating Material

DUCTILE IRON

### Flow Rate

N/A

### Outlet Type

THREADED

### Load Rating

L15 To BS EN 1253

### Threaded Joint Instructions

Apply Low Modulus Silicone to the thread of the pipe spigot & female thread within the roof outlet body. Using a flat spreading utensil, evenly spread the silicone into the threaded grooves. Insert the male into the female thread of the roof outlet body then carefully turn clockwise ensuring the thread is not "cross threading". Once fully tightened clean off excess silicone to both ends of the threaded connection.