



### Name

Frost Warm Roof drain assembly - cast iron grating, fixed 240mm circular, medium sump body with clamp, vertical threaded outlet 4" BSP

### Code

33.0104

### Description

Frost Warm Roof drain with flat 240mm circular grating, medium sump body and vertical threaded outlet 4" BSP.

Supplied with body and clamp.

Rain water outlets with flat gratings suited to warm roof construction where the waterproof membrane is located above the insulation layer on top of the roof deck.

Cast Iron Grade EN-GJL-150 to BS EN 1561:1997  
90%-97% recycled materials  
100% recyclable

Ductile Iron BS EN 1563 & 1564  
Greater than 80% recycled material  
100% recyclable

### Body Material

CAST IRON

### Body Type

N/A

### Grating Material

DUCTILE IRON

### Flow Rate

7.88

### Outlet Type

THREADED

### Grating Type

FLAT

### Load Rating

N/A

### Threaded Joint Instructions

Apply Low Modulus Silicone to the thread of the pipe spigot & female thread within the roof outlet body. Using a flat spreading utensil, evenly spread the silicone into the threaded grooves. Insert the male into the female thread of the roof outlet body then carefully turn clockwise ensuring the thread is not "cross threading". Once fully tightened clean off excess silicone to both ends of the threaded connection.