
**Body Type** 

**Flow Rate** 







### Name

Frost Floor drain 150mm circular nickel bronze grating with small sump body and threaded outlet size 4" BSP

### Code

31.0651

## **Description**

Frost floor drain assembly with height adjustable 150mm circular nickel bronze grating, small sump body and threaded outlet.

Membrane clamp & collar are an optional extra, 31.2030. Can be trapped using a removable trap (31.9510).

Quick and easy to install

Maintenance free and durable

Can be connected to all types of pipework in general use, using adaptors.

Nickel bronze for use in areas where they contribute to the aesthetic appeal of an area.

Nickel Bronze BS1400 Greater than 80% recycled material 100% recyclable

Cast iron Grade EN-GJL-150 to BS EN 1561:1997 80-97% recycled materials 100% recyclable

# **Body Material**

CAST IRON UNTRAPPED

# **Grating Material**

NICKEL BRONZE N/A

## **Outlet Type**

**THREADED** 

## **Load Rating**

L15 To BS EN 1253

### **Threaded Joint Instructions**

Apply Low Modulus Silicone to the thread of the pipe spigot & female thread within the roof outlet body. Using a flat spreading utensil, evenly spread the silicone into the threaded grooves. Insert the male into the female thread of the roof outlet body then carefully turn clockwise ensuring the thread is not "cross threading". Once fully tightened clean off excess silicone to both ends of the threaded connection.