



Name

Frost Floor drain 200mm circular ductile iron grating with large deep sump body and threaded outlet size 4" BSP

Code

31.0867

Description

Frost floor drain assembly with height adjustable 200mm circular ductile iron grating, large deep sump body and threaded outlet.

Membrane clamp & collar are an optional extra (31.2030). Can be trapped using a removable trap (31.9510).

Quick and easy to install

Maintenance free and durable

Connect body to all types of pipework in general use, using adaptors.

Ductile iron is best suited for use in unfinished and/or industrial settings.

Ductile Iron BS EN 1563 & BS EN 1564

Greater than 80% recycled material

100% recyclable

Cast iron Grade EN-GJL-150 to BS EN 1561:1997

80-97% recycled materials

100% recyclable

Body Material

CAST IRON

Body Type

UNTRAPPED

Grating Material

DUCTILE IRON

Flow Rate

N/A

Outlet Type

THREADED

Load Rating

L15 To BS EN 1253

Threaded Joint Instructions

Apply Low Modulus Silicone to the thread of the pipe spigot & female thread within the roof outlet body. Using a flat spreading utensil, evenly spread the silicone into the threaded grooves. Insert the male into the female thread of the roof outlet body then carefully turn clockwise ensuring the thread is not "cross threading". Once fully tightened clean off excess silicone to both ends of the threaded connection.